

MIAMI-DADE COUNTY PRODUCT CONTROL SECTION

11805 SW 26 Street, Room 208 Miami, Florida 33175-2474 T (786) 315-2590 F (786) 315-2599

www.miamidade.gov/pera

DEPARTMENT OF PERMITTING, ENVIRONMENT, AND REGULATORY AFFAIRS (PERA) BOARD AND CODE ADMINISTRATION DIVISION

NOTICE OF ACCEPTANCE (NOA)

La Finestra, L.C. 2790 N.W. 104 Court Miami, FL 33172

SCOPE:

This NOA is being issued under the applicable rules and regulations governing the use of construction materials. The documentation submitted has been reviewed and accepted by Miami-Dade County PERA - Product Control Section to be used in Miami Dade County and other areas where allowed by the Authority Having Jurisdiction (AHJ).

This NOA shall not be valid after the expiration date stated below. The Miami-Dade County Product Control Section (In Miami Dade County) and/or the AHJ (in areas other than Miami Dade County) reserve the right to have this product or material tested for quality assurance purposes. If this product or material fails to perform in the accepted manner, the manufacturer will incur the expense of such testing and the AHJ may immediately revoke, modify, or suspend the use of such product or material within their jurisdiction. PERA reserves the right to revoke this acceptance, if it is determined by Miami-Dade County Product Control Section that this product or material fails to meet the requirements of the applicable building code. This product is approved as described herein, and has been designed to comply with the Florida Building Code, including the High Velocity Hurricane Zone.

DESCRIPTION: Series "EKU-53" Outswing Aluminum Casement Window - L.M.I.

APPROVAL DOCUMENT: Drawing No. **FN-EKU53**, titled "EKU 53 Impact Windows", sheets 1 through 10 of 10, dated 03/16/10, with revision #1 dated 04/30/12, prepared by Bromley-Cook Engineering, Inc., signed and sealed by William D. Cook, P.E., bearing the Miami-Dade County Product Control Revision stamp with the Notice of Acceptance number and expiration date by the Miami-Dade County Product Control Section.

MISSILE IMPACT RATING: Large and Small Missile Impact Resistant

LABELING: Each unit shall bear a permanent label with the manufacturer's name or logo, city, state, model/series, and following statement: "Miami-Dade County Product Control Approved", unless otherwise noted herein.

RENEWAL of this NOA shall be considered after a renewal application has been filed and there has been no change in the applicable building code negatively affecting the performance of this product.

TERMINATION of this NOA will occur after the expiration date or if there has been a revision or change in the materials, use, and/or manufacture of the product or process. Misuse of this NOA as an endorsement of any product, for sales, advertising or any other purposes shall automatically terminate this NOA. Failure to comply with any section of this NOA shall be cause for termination and removal of NOA.

ADVERTISEMENT: The NOA number preceded by the words Miami-Dade County, Florida, and followed by the expiration date may be displayed in advertising literature. If any portion of the NOA is displayed, then it shall be done in its entirety.

INSPECTION: A copy of this entire NOA shall be provided to the user by the manufacturer or its distributors and shall be available for inspection at the job site at the request of the Building Official. This NOA revises and renews NOA# 10-0511.01 and consists of this page 1 and evidence pages E-1, E-2 and E-3, as well as approval document mentioned above.

The submitted documentation was reviewed by Manuel Perez, P.E.

MI/AMI/DADE COUNTY
APPROVED

W /1/18/12

NOA No. 12-0503.04 Expiration Date: February 27, 2018 Approval Date: July 19, 2012 Page 1

NOTICE OF ACCEPTANCE: EVIDENCE SUBMITTED

A. DRAWINGS

- 1. Manufacturer's die drawings and sections.
- 2. Drawing No. **FN-EKU53**, titled "EKU-53 Impact Windows", sheets 1 through 10 of 10, dated 03/16/10, with revision #1 dated 04/30/12, prepared by Bromley-Cook Engineering, Inc., signed and sealed by William D. Cook, P.E.

B. TESTS

- 1. Test reports on: 1) Large Missile Impact Test per FBC, TAS 201-94
 2) Cyclic Wind Pressure Loading per FBC, TAS 203-94
 along with marked-up drawings and installation diagram of a 10 ft. high, arch-top aluminum out-swinging doors, prepared by Hurricane Engineering & Testing, Inc., Test Report No. **HETI-10-3010**, dated 04/14/10, witnessed by Candido F. Font, P.E. (Submitted under previous NOA# 10-0511.01)
- 2. Test reports on: 1) Air Infiltration Test, per FBC, TAS 202-94
 - 2) Uniform Static Air Pressure Test, Loading per FBC TAS 202-94
 - 3) Water Resistance Test, per FBC, TAS 202-94
 - 4) Forced Entry Test, per FBC 2411 3.2.1 and TAS 202-94 along with marked-up drawings and installation diagram of a 10 ft. high, arch-top aluminum out-swinging doors, prepared by Hurricane Engineering & Testing, Inc., Test Report No. **HETI-10-3009**, dated 04/14/10, witnessed by Candido F. Font, P.E. (Submitted under previous NOA# 10-0511.01)
- 3. Test reports on: 1) Large Missile Impact Test per FBC, TAS 201-94
 2) Cyclic Wind Pressure Loading per FBC, TAS 203-94
 along with marked-up drawings and installation diagram of a 10 ft. high aluminum out-swinging pair of doors, prepared by Hurricane Engineering & Testing, Inc., Test Report No. HETI-10-3003, dated 04/14/10, witnessed by Candido F. Font, P.E. (Submitted under previous NOA# 10-0511.01)
- 4. Test reports on: 1) Air Infiltration Test, per FBC, TAS 202-94
 - 2) Uniform Static Air Pressure Test, Loading per FBC TAS 202-94
 - 3) Water Resistance Test, per FBC, TAS 202-94
 - 4) Forced Entry Test, per FBC 2411 3.2.1 and TAS 202-94 along with marked-up drawings and installation diagram of a 10 ft. high aluminum out-swinging pair of doors, prepared by Hurricane Engineering & Testing, Inc., Test Report No. **HETI-10-3002**, dated 04/14/10, witnessed by Candido F. Font, P.E. (Submitted under previous NOA# 10-0511.01)

Manuel Perez, P.E.
Product Control Kxaminer
NOA No. 12-0503.04

Expiration Date: February 27, 2018 Approval Date: July 19, 2012

Maure

NOTICE OF ACCEPTANCE: EVIDENCE SUBMITTED

- B. TESTS (CONTINUED)
 - 5. Test reports on: 1) Large Missile Impact Test per FBC, TAS 201-94
 2) Cyclic Wind Pressure Loading per FBC, TAS 203-94
 along with marked-up drawings and installation diagram of a 10 ft. high aluminum out-swinging pair of doors, prepared by Hurricane Engineering & Testing, Inc., Test Report No. HETI-09-2677, dated 04/14/10, witnessed by Candido F. Font, P.E. (Submitted under previous NOA# 10-0511.01)
 - 6. Test reports on: 1) Air Infiltration Test, per FBC, TAS 202-94
 - 2) Uniform Static Air Pressure Test, Loading per FBC TAS 202-94
 - 3) Water Resistance Test, per FBC, TAS 202-94
 - 4) Forced Entry Test, per FBC 2411 3.2.1 and TAS 202-94 along with marked-up drawings and installation diagram of a 10 ft. high aluminum out-swinging pair of doors, prepared by Hurricane Engineering & Testing, Inc., Test Report No. **HETI-09-2676**, dated 04/14/10, witnessed by Candido F. Font, P.E. (Submitted under previous NOA# 10-0511.01)
 - 7. Test reports on: 1) Air Infiltration Test, per FBC, TAS 202-94
 - 2) Uniform Static Air Pressure Test, Loading per FBC TAS 202-94
 - 3) Water Resistance Test, per FBC, TAS 202-94
 - 4) Large Missile Impact Test per FBC, TAS 201-94
 - 5) Cyclic Wind Pressure Loading per FBC, TAS 203-94
 - 6) Forced Entry Test, per FBC 2411 3.2.1 and TAS 202-94 along with marked-up drawings and installation diagram of an Aluminum Out-Swinging Entrance Door, prepared by Fenestration Testing Laboratory, Inc., Test Report No. FTL-4531, dated 06/01/05, witnessed by Edmundo Largaespada, P.E. (Submitted under NOA # 05-0725.03)
 - 8. Test reports on: 1) Air Infiltration Test, per FBC, TAS 202-94
 - 2) Uniform Static Air Pressure Test, Loading per FBC, TAS 202-94
 - 3) Water Resistance Test, per FBC, TAS 202-94
 - 4) Forced Entry Test, per FBC 2411 3.2.1 and TAS 202-94

along with marked-up drawings and installation diagram of an out swing wood door, prepared by Fenestration Testing Laboratory, Inc., Test Report No. **FTL-3881**, dated 08/23/04, witnessed by Edmundo Largaespada, P.E.

(Submitted under NOA # 05-0203.02)

Manuel Perez, R.E. Product Control Examiner NOA No. 12-0503.04

Expiration Date: February 27, 2018 Approval Date: July 19, 2012

La Finestra. L.C.

NOTICE OF ACCEPTANCE: EVIDENCE SUBMITTED

C. CALCULATIONS

1. Anchor verification calculations and structural analysis, complying with FBC-2007, dated 04/26/10 and revised on 08/19/10, prepared by Bromley-Cook Engineering, Inc, signed and sealed by William D. Cook, P.E.

(Submitted under previous NOA# 10-0511.01)

2. Glazing complies with ASTM E1300-04

D. QUALITY ASSURANCE

1. Miami-Dade Department of Permitting, Environment, and Regulatory Affairs (PERA)

E. MATERIAL CERTIFICATIONS

1. Notice of Acceptance No. 11–0624.01 issued to E.I. DuPont DeNemours & Co., Inc. for their "DuPont Butacite® PVB Interlayer" dated 09/08/11, expiring on 12/11/16.

F. STATEMENTS

- 1. Statement letter of conformance, complying with FBC 2010, dated April 30, 2012, signed and sealed by William D. Cook, P.E.
- 2. Statement letter of no financial interest, dated April 26, 2010, signed and sealed by William D. Cook, P.E.

(Submitted under previous NOA# 10-0511.01)

2. Laboratory compliance letter for Test Report No. FTL- 4531, issued by Fenestration Testing Laboratory, Inc., dated July 11, 2005, signed and sealed by Edmundo Largaespada, P.E.

(Submitted under NOA # 05-0725.03)

3. Laboratory compliance letter for Test Report No. FTL- 3881, issued by Fenestration Testing Laboratory, Inc., dated October 18, 2004, signed and sealed by Edmundo Largaespada, P.E.

(Submitted under NOA # 05-0203.02)

G. OTHERS

1. Notice of Acceptance No. 10-0511.01, issued to La Finestra, L.C. for their Series "EKU-53" Outswing Aluminum Casement Window – L.M.I., approved on 09/22/10 and expiring on 02/27/13.

Manuel Perez, P.E.

Product Control Examiner
NOA No. 12-0503,04

Expiration Date: February 27, 2018 Approval Date: July 19, 2012

LA FINESTRA, LC

TYPICAL CONFIGURATIONS

MAX. WINDOW SIZES SHOWN

MULTIPLE UNITS STACKED SIDE BY SIDE

SERIES: EKU 53 OUTSWING CASEMENT WINDOW (HIGH LOAD)

GLASS SCHEDULE LARGE MISSILE IMPACT RESISTANT

GL-1 = 7/16" (.454") LAMINATED 3/16" (.182") HS -.090" P.V.B. INTERLAYER (DUPONT BUTACITE) -3/16" HEAT STRENGTHENED

GL-2] = 1-1/4" INSULATED 3/16" (.182") HS -.090" P.V.B. 3/16" HS 1/2" AIR GAP 3/16" TEMPERED

GLASS CHART			
GLASS TYPE	MAXIMUM D.L.O.	MAX DESIGN L	OAD
<u>GL-1</u>	30" W x 87" H	+110.0/-110.0) PSF
	27" W x 110" H	+80.0 /-80.0	PSF
GL-2	27" W x 110" H	+80.0 /-80.0	PSF

MAX PANEL WIDTH

DLO + 9" FOR DIE # 16012 (#2) DLO + 7.62" FOR DIE # 16013 (#2A)

MAX PANEL HEIGHT

DLO + 9" FOR DIE # 16012 (#2) DLO + 7.62" FOR DIE # 16013 (#2A)

WATER INFILTRATION TEST PRESSURE - WINDOWS UP TO 96" TALL: 16.5 PSF

- WINDOWS UP TO 120" TALL: 12 PSF WITH STANDRARD THRESHOLD

MUST HAVE APPROVED MULLIONS BETWEEN EACH DOOR FRAME *(SEE ALTERNATE CONFIGURATIONS ON PAGE 2) 72" Max. Unit width 72" MAX. UNIT WIDTH SEE PAGE 5 SEE PAGE 5 FOR ANCHOR FOR ANCHOR CLUSTER QTYS: CLUSTER QTYS: 72" Max. Unit width 72" MAX. UNIT WIDTH SEE PAGE 5 SEE PAGE 5 40" [MAX. UNIT WIDTH] FOR ANCHOR FOR ANCHOR CLUSTER QTYS. CLUSTER QT MAX D.L.K 30" 21-3/4" UNIT HEIGHT 30" 120" Aax. Unit Height 1.10" (MAX D.L.O) 110. (MAX D.L.O) (MAX. D.L.O) (MAX. D.L.O) D.L.O. = 87" 96" UNIT SEE ANCHOR SCHEDULE ON PAGE 5 FOR ANCHOR SEE ANCHOR SCHEDULE SEE ANCHOR SCHEDULE SEE ANCHOR SCHEDULE LON PAGE 5 FOR ANCHOR ON PAGE 5 FOR ANCHOR ON PAGE 5 FOR ANCHOR-TYPES AND SPACING TYPES AND SPACING TYPES AND SPACING TYPES AND SPACING

NOTES:


- I. THIS SYSTEM HAS BEEN DESIGNED TO COMPLY WITH THE REQUIREMENTS
 OF THE HIGH VELOCITY HURRICANE ZONE AS DESCRIBED IN
 THE "2010 FLORIDA BULDING CODE"
- 2. THIS WINDOW SYSTEM HAS BEEN TESTED, ENGINEERED AND APPROVED FOR DESIGN PRESSURES NOT TO EXCEED THOSE SHOWN IN SCHEDULE.
- 3. BUCK, OPENINGS & BUCK FASTENERS MUST BE DESIGNED & INSTALLED

 TO WITHSTAND WIND LOADS FOR EACH APPLICATION. THE DESIGN &
 ENGINEERING OF BUCKS SHALL BE PROVIDED BY "THE ENGINEER OF RECORD"
- 4. BUCK FASTENERS MAY NOT EXCEED 16" O.C. SPACING AROUND OPENINGS.
- 5. THE SYSTEM SHOWN HEREIN WAS TESTED FOR WATER, AIR, IMPACT, CYCLIC \$ UNIFORM STATIC AIR PRESSURE TESTING IN CONFORMANCE WITH DADE COUNTY PROTOCOLS TAS-201, 202 \$ 203.
- G. ONE-THIRD INCREASE IN ALLOWABLE MATERIAL STRESS LIMITS FOR SHORT DURATION WIND LOAD NOT USED IN THE DESIGN CALCULATIONS. EXCEPT 1.6 WINDLOAD FACTOR FOR WOOD.

PRODUCT REVISED as complying with the Florida Building Code Acceptance No 12-0503, 04 Expiration Date Feb. 27, 2018

By Maule By Miami Dade Product Control





1 IMPACT

WINDOWS

WINDOWS

DATE: 03/16/2010
SCALE: NTS.
DWG. BY: LA FIN
CHK. BY:

DRAWING No.: FN-EKU53 SHEET: 1 OF 10

ALTERNATE CONFIGURATIONS UNITS MAY BE INSTALLED WITH A MIAMI-DADE COUNTY LIAN WINDOWS & DC Northwest 104th Court ami, FL 33172-2175 one (305) 599-8093 × (305) 592-4671 APPROVED MULLION BETWEEN EACH WINDOW AND/OR LA FINESTRA, FRAME. THE LOWEST DESIGN PRESSURE FOR THE WINDOW, TRANSOM OR MULLION WILL TRANSOM FRAME CONTROL, MUST HAVE SEPERATE _ PRODUCT APPROVAL MULLION ANCHORAGE AND LOAD MIAMI-DADE CO. TO BE REVIEWED AND APPROVED APPROVED MULLION BY BUILDING OFFICIAL MULLION ANCHORAGE AND LOAD MULLION ANCHORAGE AND LOAD BETWEEN UNITS TO BE REVIEWED AND APPROVED TO BE REVIEWED AND APPROVED NOTE: MUST USE MULLION SEE PG. 5 MIAMI-DADE CO. BY BUILDING OFFICIAL BY BUILDING OFFICIAL FOR ANCHOR ANCHOR CLIPS AS APPROVED MULLION CLUSTER QTYS PER N.O.A. BETWEEN UNITS -NOTE: MUST USE MULLION -40" MAX.-ANCHOR CLIPS AS W MAX. AS PER MULLION N.O.A. PER N.O.A. PER O.A. W MAX. AS I * 17.00 × 17.0 120" MAX. I 20" MAX 20" MAX ...20 SEE PG. 5 FOR ANCHOR MULLION ANCHORAGE CLUSTER QTYS. AND LOAD TO BE REVIEWED EKU-53 IMPACT WINDOWS W= W= 72" MAX. AND APPROVED BY BLDG. 40" MAX, 40" MAX. USE TRIBUTARY WIDTH "W" AS NOTED TO DETERMINE ALLOWABLE MULLION-SPANS, SEE MULLION NOA FOR DETAILS. / (MAX. AIR GAP) -OVERALL LAM. GLASS -7/16' (.457') THK. -7/16" (.457") THK. OVERALL LAM. GLASS 1-1/4" THK. = OVERALL LAM. GLASS 7/16" HS LAM + AIR + 3/16" T 8 WEDGE GASKET "EXTERIOR" WEDGE GASKET (18) "EXTERIOR "EXTERIOR wedge gasket(18 (27)GLAZING BEAD GLAZING BEAD 28 850 .850 GLASS BITE GLASS BITE .850" GLASS BITE 23 DOW CORNING 995-OR PECORA 695 9ILICONE (TYP) 7) SETTING BLOCK · SETTING BLOCK 7 DOW CORNING 995-OR PECORA 895 SILICONE (TYP) 7) SETTING BLOCK 23 DOW CORNING 995-OR PECORA 895 SILICONE (TYP) DECO WOOD TRIM ----DWG. BY: LA PRODUCT REVISED GLAZING DETAIL GL-I GLAZING DETAIL GL-1 (WITH WOOD TRIM) GLÄZING DETAIL GL-2 SCALE: NTS: MAX D.P. = +807 80 PSP as complying with the Florida Building Code Acceptance No 12-0503.04. Expiration Date Feb. 27.2018

MAX D.P. = +80/-80 PSF

DRAWING No.: FN-EKU53 SHEET:2 OF 10

MAX D.P. = +80/-80 PSF

MAX D.P. = +1107-110 PSF

SERIES EKU-53 ALUMINUM CASEMENT WINDOWS (UNIT ELEVATIONS VIEWED FROM EXTERIOR)

